

Listing of Claims

1. (Currently Amended) A method of selecting a transmission antenna in a packet transmission system having multiple antennas, comprising:
 - transmitting a first data block through a first one of a plurality of sequentially selected antennas;
 - transmitting a second data block through a second one of the plurality of antennas;
 - receiving a first signal indicating that an error occurred during transmission or reception of the first data block, the first error signal received after transmission of the second data block;
 - interrupting sequential selection of the plurality of antennas to select ~~[[a]]~~ the second one of the plurality of antennas in response to the first error signal;
 - retransmitting the first data block through the second one of the plurality of antennas, wherein the first data block is retransmitted in consecutive sequence with ~~an additional~~ the second data block ~~initially~~ transmitted by the second one of the plurality of antennas, said interruption of sequential selection of the plurality of antennas preventing the first data block from being retransmitted through the first one of the plurality of antennas;
 - resuming sequential selection of the plurality of antennas, after the first data block is retransmitted through the second one of the plurality of antennas; and
 - transmitting additional data blocks through the sequentially selected antennas.

Reply to Office Action of June 9, 2008

2. (Currently Amended) The method of claim 1, wherein the first error signal indicates whether a receiver correctly received the first data block transmitted through the first one of the plurality of antennas.

3. (Canceled)

4. (Previously Presented) The method of claim 1, wherein the first error signal is a non-acknowledgment signal transmitted from a receiver.

5. (Canceled)

6. (Currently Amended) A The method of claim 1 of selecting a transmission antenna in a packet transmission system having multiple antennas, further comprising:
sequentially selecting a plurality of antennas to transmit data, wherein a first antenna is selected to transmit a first data block and a second antenna is selected to a second data block, the first and second data blocks being consecutive data blocks;
receiving a first signal indicating that an error occurred during transmission or reception of the first data block, the first error signal received after transmission of the second data block;
interrupting sequential selection of the plurality of antennas to select the second antenna in response to the first error signal;

Reply to Office Action of June 9, 2008

retransmitting the first data block through the second antenna, wherein the first data block is retransmitted in consecutive sequence with the second data block transmitted by the second antenna, said interruption of sequential selection of the plurality of antennas preventing the first data block from being retransmitted through the first one of the plurality of antennas; and

~~transmitting a consecutive sequence of additional data blocks through the second antenna one of the plurality of antennas, the additional data blocks transmitted in consecutive sequence after retransmission of the first data block.~~

7. (Currently Amended) The method of claim 6, further comprising:

receiving a second error signal indicating that one of the additional data blocks was transmitted or received in error; and

interrupting the consecutive transmission of the additional data blocks in response to the second error signal; and

transmitting one or more subsequent data blocks through a third antenna ~~one of the plurality of antennas~~, wherein the third antenna ~~one of the plurality of antennas~~ is same ~~[[is]]~~ as the first antenna or is different from the first antenna and the second antenna.

8-10 (Canceled)

11. (Previously Presented) The method of claim 1, wherein transmission and retransmission of the data block are downlink transmissions.

12. (Previously Presented) The method of claim 1, wherein transmission and retransmission of the data block occurs through a mobile communication system.

13. (Previously Presented) The method of claim 12, wherein an open loop transmit diversity technique is used to transmit data in the mobile communication system.

14. (Previously Presented) The method of claim 13, wherein the open loop transmit diversity technique is a TSTD (time switched transmit diversity) technique.

15. (Previously Presented) The method of claim 1, wherein the first error signal is received based on an ARQ (automatic repeat request) from a receiver.

16. (Currently Amended) A method of selecting a transmission antenna in a packet transmission system having multiple antennas, comprising:

sequentially selecting a plurality of antennas for transmission of data, wherein transmitting a first data block is transmitted to a receiver through a first antenna and a second data block is transmitted through a second antenna;

checking a first response signal of the receiver, the first response signal received after transmission of the second data block; and

Reply to Office Action of June 9, 2008

if the first response signal is a retransmission request signal, retransmitting the first data block through [[a]] the second antenna, wherein the first data block is retransmitted in consecutive sequence with ~~an additional~~ the second data block initially transmitted by the second antenna;

resuming sequential selection of the plurality of antennas after the first data block is retransmitted through the second antenna; and

transmitting additional data blocks through the sequentially selected antennas.

17. (Previously Presented) The method of claim 16, further comprising:

sequentially selecting the multiple antennas including the first antenna and the second antenna, said sequential selection taking place before the first response signal is checked.

18. (Canceled)

19. (Currently Amended) A ~~The method of claim 16, further~~ comprising

sequentially selecting a plurality of antennas for transmission of data, wherein a first data block is transmitted to a receiver through a first antenna and a second data block is transmitted through a second antenna;

checking a first response signal of the receiver, the first response signal received after transmission of the second data block;

if the first response signal is a retransmission request signal, retransmitting the first data block through the second antenna, wherein the first data block is retransmitted in consecutive sequence with the second data block initially transmitted by the second antenna;

transmitting a consecutive sequence of additional data blocks through the second antenna, the additional data blocks transmitted in consecutive sequence after retransmission of the first data block.

20. (Currently Amended) The method of claim 19, further comprising:

receiving a second response signal indicating that one of the additional data blocks was transmitted or received in error; and

interrupting the consecutive transmission of the additional data blocks in response to the second response signal; and

transmitting one or more subsequent data blocks through a third antenna, wherein the third antenna is same ~~[[is]]~~ as the first antenna or is different from the first antenna and the second antenna.

21-23 (Canceled)

24. (Previously Presented) The method of claim 16, wherein transmission and retransmission of the data block are downlink transmissions.

25. (Previously Presented) The method of claim 16, wherein an open loop transmit

Reply to Office Action of June 9, 2008

diversity technique is used to transmit data in the mobile communication system.

26. (Previously Presented) The method of claim 25, wherein the open loop transmit diversity technique is a TSTD (time switched transmit diversity) technique.

27. (Previously Presented) The method of claim 16, wherein the first response signal is received based on an ARQ (automatic repeat request) from a receiver.

28. (Original) The method of claim 27, wherein the response signal is ACK or NACK signal according to ARQ.

29. (Canceled)